

Subpart 71.30—Reinspection**§ 71.30-1 When made.**

In general, at least three reinspections shall be made on each vessel within one year. These reinspections will be made at approximately equal intervals between annual inspections. In the case of vessels with a seasonal schedule, reinspections will be made during the operating season if practicable.

[CGFR 65-50, 30 FR 16895, Dec. 30, 1965, as amended by CGD 95-028, 62 FR 51203, Sept. 30, 1997]

§ 71.30-5 Scope.

(a) The inspector shall examine all accessible parts of the vessel's hull, machinery, and equipment to be assured that it is in a satisfactory condition.

(b) In general, the scope of the reinspection shall be the same as for the annual inspection, but will be in less detail unless it is determined that major change has occurred since the last annual inspection.

§ 71.30-10 Inspector not limited.

(a) Nothing in this subpart shall be construed as limiting the inspector from making such tests or inspections as he deems necessary to be assured of the safety and seaworthiness of the vessel.

(b) [Reserved]

Subpart 71.40—Inspection After Accident**§ 71.40-1 General or partial survey.**

(a) A survey, either general or partial, according to the circumstances, shall be made every time an accident occurs or a defect is discovered which affects the safety of the vessel or the efficacy or completeness of its life-saving appliances, fire-fighting or other equipment, or whenever any important repairs or renewals are made. The survey shall be such as to insure that the necessary repairs or renewals have been effectively made, that the material and the workmanship of such repairs or renewals are in all respects satisfactory, and that the vessel com-

plies in all respects with the regulations in this subchapter.

(b) [Reserved]

Subpart 71.45—Sanitary Inspections**§ 71.45-1 When made.**

(a) An inspection of passenger and crew quarters, toilet and washing spaces, serving pantries, galleys, etc., shall be made, in general, at least once in every month. If the route of the vessel is such that it is away from a United States port for more than one month, an inspection shall be conducted at least once every trip.

(b) [Reserved]

Subpart 71.50—Drydocking**§ 71.50-1 Definitions relating to hull examinations.**

As used in this part—

Adequate hull protection system means a method of protecting the vessel's hull from corrosion. It includes, as a minimum, either hull coatings and a cathodic protection (CP) system consisting of zinc anodes, or an impressed current CP system.

Alternative Hull Examination (AHE) Program means a program in which an eligible vessel may receive an initial and subsequent credit hull examination through a combination of underwater surveys, internal examinations, and annual hull condition assessment.

Drydock examination means hauling out a vessel or placing a vessel in a drydock or slipway for an examination of all accessible parts of the vessel's underwater body and all through-hull fittings and appurtenances.

Internal structural examination means an examination of the vessel while afloat or in drydock and consists of a complete examination of the vessel's main strength members, including the major internal framing, the hull plating, voids, and ballast tanks, but not including cargo, sewage, or fuel oil tanks.

Remotely operated vehicle (ROV) team, at a minimum, consist of an ROV operator, a non-destructive testing inspector, an ROV tender or mechanic, and a team supervisor who is considered by